





ARMSTRONG RETAIL 12 mm

- Armstrong RETAIL offers a smooth, unperforated contemporary visual that provides energy savings due to its high level of light reflectance
- Excellent light reflectance (87%)
- Ideal for retail environments



knaufceilingsolutions.com



ARMSTRONG RETAIL 12 mm



Edge details		Board										
		ĵ										
		<u>24</u>										
Thickness (mm)	 ✓ ↑ 	12										
Dimensions (mm)	k ,)	600 x 600 1200 x 600										
System		Exposed den Exposed - Bo Exposed - Co	andraster, der	ystem C mountable - Sy puntable - Syste	ystem I.3 em F.3							
Weight	Kg	3.1 kg / m²										
Colour	6	White										
Sound absorption		EN ISO 354			_							
		α _w = 0.15(L) Frequency f		60 11654 - Cl	ass E	125	250	500	1000	2000	4000	
			(112)			0.30	0.25	0.15	0.10	0.10	0.20	
		NRC = 0.15	as per ASTM	C 423								
Sound attenuation		EN ISO 108 D _{n,f,w} = 31 de		SO 717-1								
Fire reaction	T	Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per FZ 123										
Light reflectance	7	87 %										
Thermal conductivity	H	λ = 0.060 V	V/m K as p	er EN 12667								
Humidity resistance	•	70% RH										
Indoor air quality		A+	E1									
Cleanability		Z	<u></u>									
Sustainability		6% EN 150 14021	BIOROLLIBLE WOOL									

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.

