

TENAX JAMAICA



KNITTED NET

PHYSICAL AND DIMENSIONAL CHARACTERISTICS

Polymer		HDPE					
Mesh shape		QUADRANGULAR					
Packaging		ROLLS WRAPPED WITH POLYETHYLENE FILM					
Color		GREEN					
Shading factor	%	70					
Type of covering	%	80					
Unit weight	g/m ²	75					
Net width	m	1,00	1,50	2,00	3,00	4,00	6,00
Roll width	m	1,00	1,50	1,00	1,50	2,00	3,00
Roll length	m	100,0	100,0	100,0	100,0	100,0	100,0
Covered area	m ²	100,0	150,0	200,0	300,0	400,0	600,0
Roll diameter	m	0,22	0,22	0,30	0,30	0,30	0,30
Roll volume	m ³	0,05	0,08	0,10	0,14	0,19	0,28
Roll weight	kg	8,0	12,2	15,5	22,5	29,5	44,0
Inner tubular diameter	mm	76,5					

MECHANICAL CHARACTERISTICS

Tensile strength MD	kN/m	3,5
Yield point elongation MD	%	30,0

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values.

TENAX nets are thermoplastic products subjected to shrinkage and deformations. MD: longitudinal direction. TD: transversal direction.

Tenax SpA Quality System has been assessed and registered in agreement with ISO 9001:2000 Standard.

TENAX®

www.tenax.net