

iD INSPIRATION CLICK HIGH TRAFFIC 70/70^{PLUS}

TECHNICAL DATA

Certification & classification	Standards	iD Inspiration Click High Traffic 70/70 ^{PLUS}
Type of floor covering	EN ISO 10582	-
Classification	EN ISO 10874	Commercial: 34 Industrial: 43
Technical characteristics		
Total thickness	EN ISO 24346	5.0 mm
Wear layer thickness	EN ISO 24340	0.7 mm
Total weight	EN ISO 23997	8350 g/m ²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	Planks	19,05 x 121,10 cm 24,05 x 149,10 cm
	Tiles	32,38 x 60,10 cm 49,05 x 99,10 cm
Surface treatment (PUR)		Yes - TopCleanXP™
Beveled edges		Yes
Embossing in Register		Yes
Technical performances		
Dimensional stability	EN ISO 23999	Required value ≤ 0.15%
Reaction to fire	EN 13501-1	B _n -s1 loose laid over concrete substrate
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Reduction of in-room impact noise	EN ISO 31-074	Class C (L _{n,e,w} < 85 dB)
Impact sound reduction	EN ISO 717-2	ΔL _w = 5 dB
Thermal resistance	ISO 10456	0,04 m ² K/W
Light fastness	EN ISO 105-B02	≥ 6
Slip resistance	DIN 51130 EN 13893	R9 / R10 depending on embossing μ ≥ 0,30
Chemical resistance	EN ISO 26987	Very good (1)
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete ≥ 10 ⁹ Ohm
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C
TVOC emissions after 28 days	EN 16516	≤ 10 μg/m ³ *

* Platinum TIAQ.

The above information is subject to modification for the benefit of further improvement. (06/17).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for these instructions. CE Marking is available on our website www.tarkett.com

CUSTOMS TARIFF : 4820 5000 00

